

Strengths

-  Tolerance 0~+3%
-  High Transmission, low Iron Tempered Glass
-  Plug&Play Connectors
-  Bypass Diodes Protection
-  Salt Mist Test And Ammonia Resistance Test

Warranty

-  Manufacturing 12 Years
-  Power Production
95%: 5 years 90%: 12years
85%: 18years 80%: 25years


Insurance

-  Insured By CHUBB

Certificates




PHYSICAL CHARACTERISTICS unit:mm



SR MODULE

-  SR-P648200-B
-  SR-P648190-B
-  SR-P648180-B
-  SR-P648195-B
-  SR-P648185-B



Dimensions	(mm)	1316×992×40
Weight	(kg)	14.5
Loading Capacity		376 pcs/20' GP
		800 pcs/40' GP

Sunrise Solartech Co.,Ltd.

No.20 Tongzi River West Road,zhonglou Development Zone ,
Changzhou 213023 Jiangsu P.R.china.
Tel:+86(519)8390 6502
Fax:+86(519)8390 6508
E-mail:info@srsolartech.cn
Http://www.srsolartech.cn

Specifications

Module Type		SR-P648200-B	SR-P648195-B	SR-P648190-B	SR-P648185-B	SR-P648180-B
Maximum Power	Pm(W)	200W	195W	190W	185W	180W
Tolerance	(%)	0~+3	0~+3	0~+3	0~+3	0~+3
Open Circuit Voltage	Voc(V)	29.80	29.72	29.62	29.48	29.40
Short Circuit Current	Isc(A)	8.94	8.77	8.56	8.38	8.18
Maximum Power Voltage	Vm(V)	24.04	23.99	23.90	23.81	23.72
Maximum Power Current	Im(A)	8.32	8.13	7.95	7.77	7.59
Module Efficiency	(%)	15.30	15.00	14.60	14.20	13.80
Solar Cell Efficiency	(%)	17.60	17.20	16.70	16.30	15.80
Cell Type	(mm)	156×156(Poly-Crystalline Silicon)				
Number of Cells	(Pcs)	48(6×8)				
Maximum System Voltage	(V)	DC1000				
Temp. Coeff.of Voc	(%/°C)	-0.33				
Temp. Coeff.of Isc	(%/°C)	0.055				
Temp. Coeff.of Pm	(%/°C)	-0.44				
Operating Temperature	(°C)	-40 to 85				
Nominal Operating Cell Temperature(NOCT)	(°C)	45±2				
Max.Series Fuse	(A)	14				
Wind Bearing	(Pa)	2400				
Pressure Bearing	(Pa)	5400				
STC(Standard Test Conditions):1000W/m² AM=1.5 25℃						

Electrical Characteristics

		1000 W/m ²	800 W/m ²	600 W/m ²	400 W/m ²	200 W/m ²	100 W/m ²
SR-P648200-B	Vmpp	24.04	23.92	23.68	23.11	22.36	21.76
	Impp	8.32	6.09	4.64	3.13	1.62	0.82
SR-P648195-B	Vmpp	23.99	23.87	23.63	22.03	22.31	21.71
	Impp	8.13	5.99	4.52	3.07	1.59	0.81
SR-P648190-B	Vmpp	23.90	23.78	23.54	22.75	22.23	21.63
	Impp	7.95	5.85	4.41	3.02	1.54	0.79
SR-P648185-B	Vmpp	23.81	23.69	23.45	22.86	22.14	21.55
	Impp	7.77	5.71	4.31	2.94	1.51	0.77
SR-P648180-B	Vmpp	23.72	23.60	23.36	22.77	22.06	21.47
	Impp	7.59	5.57	4.23	2.88	1.48	0.75

